



PRODUCT PROFILE

DESCRIPTION

SACRIFICIAL GRAFFITI GARD® SYSTEM is a specially formulated and blended water-based resin for optimum performance as a protective sacrificial system over new or previously painted substrates.

FEATURES

- Water-Based Formulation
- Blend of Waxes and Resins

BENEFITS

- Protects Underlying Surface
- Quickly Reapplied
- Easy-To-Remove Graffiti
- Immediate Protection

RECOMMENDED PRIMERS/SUBSTRATES

XL 70®, TEX-COTE® 300, TEX-COTE® 400, TEX-COTE® 600, RAINSTOPPER®, RAINSTOPPER® 500, RAINSTOPPER® Concrete Stain, Concrete, Metal, Cement Plaster, Wood, Block, Brick, and other manufacturer-approved surfaces.

NOTE: Masonry, including Mortar, Concrete, and Cement Plaster, **MUST** be cured a minimum of 28 days prior to applying the SACRIFICIAL GRAFFITI GARD®.

PRODUCT APPLICATION

APPLICATION EQUIPMENT

SACRIFICIAL GRAFFITI GARD® System may be rolled on or applied with commercial-grade airless. Tip size .015 to .017. The applicator must create a continuous pinhole-free film.

GENERAL/SURFACE PREPARATION

All surfaces must be sound and clean. Old painted surfaces should be properly adhered to the substrate. Surface contaminants such as dust, environment dirt, mildew, form oils and loose substrate shall be thoroughly removed with the use of water-blasting, abrasive-blasting, wire brushing, or scraping, as approved by manufacturer.

Graffiti-marred surfaces may need to be treated with Graffiti Stain Blocker and TEX-COTE® Pigmented TY•COTE, prior to application of SACRIFICIAL GRAFFITI GARD®.

Murals, logos, or wall treatments that may be sensitive to hot water-blasting should be protected with TEX-COTE® Clear TY•COTE, prior to the application of SACRIFICIAL GRAFFITI GARD®.

Allow a 24-hour cure of the TY•COTE prior to the application of the SACRIFICIAL GRAFFITI GARD®.

APPLICATION RATE

Application rates will vary with the porosity of the substrate from 150-250 square feet per gallon. Application must be a continuous pinhole-free film.

APPLICATION

A sample wall is recommended for field approval by architect, manufacturer's representative and contractor. Provide a properly prepared, dry surface for the SACRIFICIAL GRAFFITI GARD® System.

Inspect opened container, mix thoroughly prior to each application. Apply a uniform, pinhole-free, continuous film over the entire surface. If runs or sags occur, immediately brush them out to even the film.

CLEAN-UP

- **For Dry Material:** Use Mineral Spirits, Xylol, or Most Paint Thinners
- **For Wet Material:** Use Water.

REMOVAL

SACRIFICIAL GRAFFITI GARD® may be removed using a hot water blaster. Water temperature should be 170°F to 180°F; water pressure should be approximately 900 to 1200 PSI. Keep pressure as low as possible to avoid damaging underlying surface.

BEST PERFORMANCE

IMPORTANT STEPS

- SACRIFICIAL GRAFFITI GARD® System shall be applied under ideal weather conditions.
- Rain is not imminent, surfaces are not wet or frozen.
- Temperature is within 50°F to 100°F range (10°-37.7°C).
- All incompatible form oils, release agents, chalking paint, and laitances must be removed prior to application.
- Retaining walls, planter boxes, etc. should be waterproofed with a below-grade asphalt-type sealer on side of wall exposed to backfill.
- SACRIFICIAL GRAFFITI GARD® System is above-grade only. Do NOT use below-grade or on horizontal surfaces exposed to ponding water.
- TEX-COTE LLC does NOT promote or recommend coating the sealant joints, nor is the sealant compound an approved substrate.

ORDER INFORMATION

QUANTITY & COLORS

TY•COTE PIGMENTED is available in TEX-COTE® Standard Colors or special colors upon request.
SACRIFICIAL GRAFFITI GARD® is a clear sealer.

PACKAGING

Available in one (1), five (5), thirty (30), and fifty-five (55) gallon containers.

APPLICATION RATE

Apply at a rate of 150 to 250 square feet per gallon depending upon porosity. Application must be a continuous pinhole-free film.

SHELF LIFE

12-Month Shelf Life under proper conditions:

- Containers are sealed, upright and airtight in a dry place.
- Maintain temperature of 45°F to 100°F (7°C to 37.7°C); AVOID FREEZING.
- Skins formed on surface of material must be removed prior to moving containers or mixing.

SAFETY

LIQUID

- Avoid contact with eye, skin, and clothing.
- Wash thoroughly after handling.
- In case of eye contact, flush immediately with large quantities of water for at least 15 minutes.
- Seek medical attention if blurring or redness continues.

CURED FILM

- Cured SACRIFICIAL GRAFFITI GARD® is a blend of non-hazardous waxes.
- Removal of this coating is allowed to enter sanitary sewers as a non-hazardous substance when removed by hot water-blasting.
- Check with local authorities for local or state regulations.

VOC COMPLIANCE

All TEX-COTE® products comply with federal Volatile Organic Compound (VOC) rules and regulations.

Please contact your nearest TEX-COTE LLC office for assistance on the local and state VOC compliance in the area of intended use.

WARRANTY

Upon completion of the application of the coating in accordance with the manufacturer's recommendations, TEX-COTE LLC will extend its limited commercial warranty for product replacement as a result of a defect in the material. The manufacturer must be notified prior to the application of the coating and the application must be in compliance with the manufacturer's recommendations for installation. TEX-COTE LLC shall have no obligation to contribute to or otherwise participate in labor or cost associated with effecting repairs. Specimen copy of material warranty is available upon request.

Corporate HQ & East Coast Facility

2422 E. 15th St., Panama City, FL 32405 | 800-454-0340 | 850-769-0347 | Fax 850-913-8619

South Florida Sales Office

7000 W. Palmetto Park Rd., Ste 210-W14, Boca Raton, FL 33433 | 954-581-0771 | Fax 954-581-9516

West Coast Facility

417 E. Weber Ave., Compton, CA 90222 | 323-233-3111 | Fax 310-438-2873